



Standard Zugspannzangen

Standard Drawback Collets

Artikel Nr. item no.	OZ-Nr.	D1 [mm]	D2 [mm]	L [mm]	Konuswinkel "W" spindle cone angle "W" [°]	G	Größter Durchgang [mm] max capacity [mm]	
							durchgehend throughhole	stop
0302...	OZ 201	8	12,5	35,5	20	6,85 x 40 Pitch	4,5	7
0319...	OZ 1468	12	18	63,4	20	Tr 12 x 1	8	9,5
0324...	OZ 233	15	21,5	56	20	M13 x 1	9	13
0349...	OZ 190	20	26,3	73	15	S 20 x 1,66	15	20
0351...	OZ 1470	20	28	84,7	20	Tr 20 x 1,5	15	17
0355...	OZ 1256	20	28	122,7	17°30'	S 20 x 2	12,5	18
0358...	OZ 234	23	32	86,5	20	21,25 x 1	16	20
0359...	OZ 1471	23	32	93,4	20	Tr 23 x 1,5	18	20
0364...	OZ 1588	25	33,7	97,6	15	S 25 x 15 Pitch	18,5	22
0367...	OZ 1472	28	38	106,7	20	Tr 28 x 1,5	22	24
0385...	OZ 5011	31,75	37,5	87	10	1,245" - 20	26	28
0386...	OZ 1473	32	45	116	20	Tr 32 x 1,5	27	29